

Litepanels Ringlite®

Ringlite Mini® Models: 5600°K • 3200°K

Measuring 10.5" in diameter, 2" thick and weighing 3.5 pounds, Ringlite Mini provides luminous, soft, directional output in a cost-effective, versatile package. This low-profile, lightweight professional lighting tool is equally at home on or off camera, mounted on a stand, wall, or elsewhere.

Three Channels, Minimal Shift when Dimming

The Ringlite Mini employs powerful LEDs laid out in a tightly plotted grid. Lighting is divided into three separate user-selectable segments (bottom, middle, top). A separate, master dimmer circuit controls channels of output. On the back, four toggle switches regulate power and control upper, center and lower illumination. An ergonomic integrated control knob allows for instant dimming from 100%-0 with minimal shift in color, plus there is remote dimming capability. Completely flicker and heat free, the system can be moved in comfortably close to a subject, for soft, wrap-around light. A set of 6 interchangeable conversion and diffusion filters is available.



Ringlite Mini fits most popular cameras

Power Efficient

This ultra-efficient LED light source draws just 3.5 amps (40W @12VDC). Power is provided by an external 100-240VAC international AC adapter. Equipped with an XLR power connector cable, the unit can be run off of 12-30VDC battery sources such as the Litepanels Backpack PowerCell.

Specifications

- Outer Diameter: 10.5" (26.7 cm)
- Inner Diameter: 5" (12.7 cm)
- Weight: 3.5 Lbs (1.58 kg)
- Depth: 2" (5.1 cm) thick
- Power Draw: 40 Watts/3.5 amps @ 12VDC
- Power Supply: 12-30V, AC Adapter 100-240V
- 6 piece filter set: 1/8, 1/4, 1/2, full CTO; 250, Lt.
- Grid diffusion

Advantages

- Soft & directional
- Lightweight, slimline design
- Dims 100% to 0 with minimal color shift
- 3 user-selectable circuits
- Heat free & flicker free


Options

- Backpack PowerCell (1.75 hrs.)
- Mounting brackets
- Correction/diffusion gel filter
- Remote Controls

Ringlite Cinema® Models: 5600°K • 3200°K



Anastas Michos, ASC chose LED Ringlite for "The Women"



Theo Van de Sande, ASC handholds Ringlite for just the right kick

Employing an array of seventy-two segments of ultra-powerful LEDs laid out in a precisely spaced concentric design, this ingenious illumination tool produces an even quality of luminous, soft, directional output.

Ultimate Control at Your Fingertips

A favorite of Hollywood, Ringlite Cinema controls lighting through three separate, adjustable circuits. Operators can select 24, 48 or the full 72 LED segments. Thanks to its heat free and flicker free output, Ringlite can be moved in close with no discomfort to the subject.

The system's ergonomic integrated dimmer control enables instant dimming from 100% to 0 with minimal shift in color. For additional lighting refinement, a set of interchangeable correction/diffusion gels is available. They fit neatly on the face of the unit, held in place by a translucent cover.

RINGLITE CINEMA 5600° K FLOOD PHOTOMETRICS

Distance	Footcandles	LUX
5 ft./ 1.5m	240	2600
10 ft./ 3m	64	690
15 ft./4.5m	34	370

RINGLITE MINI 5600° K FLOOD PHOTOMETRICS

Distance	Footcandles	LUX
5 ft./ 1.5m	100	1100
10 ft./ 3m	26	280
15 ft./4.5M	13	140